

S-SERIES RUN DOWN ADAPTERS

- It is designed to serve as a joint simulator for testing power-driven torque control tools. It provides consistent and reliable torque readings
- Run down simulation for 'soft joint'
- The adapter is mounted inline between the tool's drive and the EZ-TorQ's transducer
- Non-rotating body for improved safety
- Compact size and lightweight
- Operates in clockwise direction only. After each run down, the RDA should be completely backed-up



Torque Ranges

| Models | Item # | American | S.I. | Input Drive | Output Drive |
|----------|--------|---------------------|-------------------|-------------|--------------|
| RDA-S0 | 070844 | 0.3–3 lbf.in | 3.4–33.9 cN.m | 1.5mm Hex | 1/4" F/Sq |
| RDA-S1.5 | 070845 | 0.5–5 lbf.in | 5.6–56.5 cN.m | 2.5mm Hex | 1/4" F/Sq |
| RDA-S10 | 070835 | 1 - 6.1 lbf.in | 11.3 - 68.6 cN.m | 4mm Hex | 17mm Hex |
| RDA-S15 | 070833 | 2.1 - 11.5 lbf.in | 25.5 - 129.5 cN.m | 6mm Hex | 17mm Hex |
| RDA-S75 | 070834 | 6.9 - 52.1 lbf.in | 78.5 - 588.4 cN.m | 6mm Hex | 17mm Hex |
| RDA-S200 | 070840 | 15.6 - 121.5 lbf.in | 1.8 - 13.7 N.m | 6mm Hex | 17mm Hex |
| RDA-S400 | 070839 | 48.6 - 286.4 lbf.in | 5.5 - 32.4 N.m | 10mm Hex | 17mm Hex |
| RDA-S600 | 070841 | 48.6 - 434 lbf.in | 5.5 - 49 N.m | 10mm Hex | 17mm Hex |

Related Products



Electric Screwdrivers

Electric torque screwdrivers increase productivity and enhance product quality through precision torque control and user comfort. The electric screwdriver automatically shuts off once the preset torque is achieved.



Torque Analyzers

Measure and calibrate tools with a torque analyzer.