

## THIN FILM POROSITY TESTING

### Complies with the requirements of

AS3894.1-2002 (Wet Sponge Testing); ASTM G62-07; ASTM G6-07; ASTM D5162-08; NACE RP0274-2004; NACE SP0188-2006

### Features

- LED display of voltage
- Internally mounted 9v battery  
Low battery condition
- LED indicator Audible and visual fault alarms
- Telescopic handle for user comfort  
(extends to 1.2m)
- Large probe head (230x 40mm) and wider sponge gives faster tests
- Earphone jack to allow testing in noisy environments (earphone not supplied)

### Application

- Uses the wet sponge method to detect pinholes in coatings

### Models

- Selectable 9; 67.5 or 90v test voltage

***We highly recommend that coatings over 150µm, or coatings in corrosive environments, be high voltage porosity tested.***

**Made in AUSTRALIA**



### Specifications

Range: 0 to 500µm  
Operating temperature: 0 to +50°C  
Test Voltage: 9, 67.5 and 90V  
Telescopic Probe length: 350mm to 1.2m  
Power supply: 9v Battery

Dimensions: 210 x 75 x 35mm

Weight: 350g

### Kit comprises

- Unit and Handle including Sponge
- Belt/pocket clip
- Seven metre earth lead and clip
- Carry case
- Instruction manual with Calibration certificate

Ordering Information: Part No. WETSPONGE